



Model: C12B
Diameter range of service: DN50 - DN110
Dimensions: Φ 23mm x 180
 Passage of elbows: ≥ 35 mm
 Materials: housing in stainless steel, lens in sapphire crystal
 Focal length: 5 to 15 cm, fixed
 Resolution: 0.4 mega-pixel
 Lighting: 8 LEDs
 Waterproof: IP68, 1 bar Max.
 Operational temperature: -20°C to 55°C

Camera Head C12B

Diametro cabeza 23 mm auto ó 25mm

Sonda Empuje 40 Metros

Cable Reel CR12

Cable material: fibre glass
 Diameter & length: Φ 4.8 mm & 30 m
Contador de metros en pantalla
 Meter counting: in option for 30 m and 40 m cables
 Power supply: by the control station
 Protection rating: splash-proof
 Operational temperature: -28°C to 50°C
 Dimensions: 32 x 32 x 11 cm

EQUIPO CAMARA 12mm INSPECCION TUBERIAS

Screen: 7" TFT, 800 x 480 PX resolution
 Autonomy: ≥ 4 h
 Power supply: 220 VAC / rechargeable Li-ion battery
 Photo / video(JPEG / AVI) / audio recording
 Ports: 1 x USB, 1 x SD, 1 x video input
 Case: small, ABS, splash-proof
 Weight & dimensions: 2,5 kg, 27 x 22 x 10 cm

Control Station CST7M

diametro 23mm Autonivel

Largo= 40metros

1 x DVR remote control, 1 x charger/AC adaptor, 1 x connecting cable, 1 x centralizer, 1 x built-in Li-ion battery, 1 x notice

KAMI

OTROS INSTRUMENTOS y EQUIPOS TECNICOS:

Grabe codigo QR en su movil=

- CAMARAS TERMOGRAFICAS: varios modelos y marcas ,Hasta 640x480 , 1500°C , VideoRadiometrico ,Humedad, etc.**- VIDEOSCOPIOS desde 1.9mm - articulados .etc. y CAMARAS INSPECCION TUBO** empuje desde 13mm a ROBOT**- AGUA y ANTI FUGAS:** DETECTOR FUGAS AIRE , GEOFONO AGUA , LOCALIZADORES y HIGIENE Ultravioleta UV-C**- PREVENCIÓN RIESGOS:** Vibrometros ,Sonometros ,RADIACIONES Electromagneticas y Opticas ,AIRE, Fuerza, etc.**- INSTRUM. MEDIDA** .- Analizador COMBUSTION , °C,%H,CO,CO2 ,DataLogger, Distancia ,Velocidad ,MICROSCOPIOS, etc

www.gimateg.com

CAMARA 23 mm Auto x40 m para TUBOS

gimateg@telefonica.net

GIMATEG

www.gimateg.com

Calle Antonio Cusido 136 bajos 08208 SABADELL (Barcelona)

Tel.- 937071855

627152432

Fax.-937247140